



PC 5T / PC 8T Plastic ceiling loudspeakers

TECHNICAL SPECIFICATIONS




PC 5T / PC8T

PC T - ABS plastic ceiling loudspeakers with built-in 100V transformer with power taps.


Excellent full range sound, used where a combination of high quality background music and public address are required. These loudspeakers are designed to be quickly and simply installed into false ceilings. Wide sound dispersion and innovative neutral design makes these loudspeakers useful in a variety of applications, restaurants, bars, cafes, shops, offices, moles and large public spaces for background music and speech announcements.

| | PC 5T | PC 8T |
|------------------------|---|---|
| Rated power | 10 W | 20 W |
| Transformer power taps | 10 W - 5 W - 2,5 W - 1,25 W | 20 W - 10 W - 5 W - 2,5 W |
| Sensitivity | 88 dB (1 W/1 m) | 88 dB (1 W/1 m) |
| Maximum SPL | 98 dB (Pmax/1 m) at 15694 Hz | 101 dB (Pmax/1 m) at 15249 Hz |
| Frequency response | 90 Hz – 20 kHz | 80 Hz – 20 kHz |
| Dispersion at 1000 Hz | 120° conical | 120° conical |
| Driver dimensions | 5" (130 mm) woofer, 0,5" (13 mm) tweeter, coaxial | 8" (200 mm) woofer, 0,5" (13 mm) tweeter, coaxial |
| Dimensions | ø 190 mm × 70 mm | ø 245 mm × 95 mm |
| Weight | 1,1 kg | 2,1 kg |
| Material | Plastic | Plastic |
| Colour | White (RAL 9016) | White (RAL 9016) |

PC 5T



PC 8T



unit: mm